

Follow these steps to connect a PlayStation 2 to the Northwood network:

1. Connect the Ethernet cable to the Playstation 2.
2. Start the PlayStation 2 and load the Network Adaptor Startup disc included in the Network Adaptor package.
3. Once the disc has loaded, press “X” to enter the ISP SETUP.
4. Once the setup process has loaded, press “X” to continue.
5. Your PlayStation will search for the network adaptor. After the network adaptor has been found, press “X” to continue.
6. Press “X” again to continue.
7. Select “NEW” and then press “X” to continue.
8. Using the on-screen keyboard, enter the name NORTHWOOD for your new network configuration and press the “X” button.
9. You will be asked if you subscribe to an Internet Service Provider. Select “YES”.
10. On the next screen, highlight “High Speed Connection (Cable or DSL)” and press the “X” button.
11. Select “Automatic Settings (Cable or DSL)” and press “X”.
12. Select “No” when asked if your ISP requires a User ID and Password.
13. Select “No” when asked if you need to enter a DHCP Host Name.
14. Once the network connection test is successful press “X” to save the configuration to the memory card.
15. The network configuration will now be saved to the memory card. Do not remove the network card while this information is being saved.

Your PlayStation should now be configured to the Internet and you should now be able to start playing online. Press “X” to return to the main menu.

How to Find a MAC Address for the Playstation 3

From the PS3 main menu screen, follow these steps:

1. Navigate to the **Settings** icon (located on the far left).
2. Press the "**X**" button.
3. Navigate up/down until you see the **System Settings** icon.
4. Press the "**X**" button.
5. Scroll up/down until you see **System Information**.
6. Press the "**X**" button.

The MAC address will be displayed. It will consist of alphanumeric characters and have the format xx-xx-xx-xx-xx-xx.